



1590L 15-inch LCD

Open-Frame Touchscreen



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1590L 15-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 1590L provides stable, drift-free operation with outstanding image clarity and light transmission for accurate touch responses and vivid images. Instantly grabbing and holding users' attention, the open-frame touchscreen is perfect for kiosks, casino and amusement, retail self-service, and industrial automation environments.

Choice of Elo touch technologies:
Standard bezel: IntelliTouch[®] SAW, SecureTouch[®] SAW and AccuTouch[®] five-wire resistive
Zero-bezel: TouchPro[™] PCAP

PCAP 2GS (two glass solution) offers pristine optical clarity and touch durability

10 touch projected capacitive with Thru-glass capabilities that passes UL-60950 & IK-07 impact testing

1590L 15-inch Open-Frame Touchscreen

| Specifications | |
|------------------------------|--|
| Model | 1590L |
| Color | Black |
| Active Display Area | 11.97" x 8.98" / 304.1mm x 228.1mm |
| Diagonal | 15" |
| Aspect Ratio | 4:3 |
| Dimensions | Bezel: 13.24" x 10.41" x 1.65" / 336.4mm x 264.4mm x 41.9mm Zero-Bezel: 14.09" x 11.22" x 1.40" / 358mm x 284.9mm x 35.6mm |
| Native Resolution | 1024 x 768 at 60, 75 Hz |
| Other Supported Resolutions | 640 x 480 at 60 Hz; 720 x 400 at 70 Hz; 800 x 500 at 60 Hz; 800 x 600 at 56, 60Hz |
| Number of Colors | 16.2 million |
| Number of Touches | Single-touch and 10-touch |
| Brightness (typical) | LCD Panel: 250 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits; SecureTouch: 220 nits; Projected Capacitive (PCAP): 225 nits |
| Response (typical) | 16 msec |
| Viewing Angle | Horizontal: 80°/160°; Vertical: 70°/140° |
| Contrast Ratio | 700:1 |
| On-Screen Display | Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power |
| Input Video Format | Analog VGA and DisplayPort |
| Input Video Signal Connector | Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of Display Port video input |
| Scanning Frequency | Horizontal: 30 - 60 kHz; Vertical: 50 - 75 Hz |
| Power | External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth) Monitor input power signal specifications: 12VDC +/- 5% |
| Power Consumption | ON (monitor + power brick): 12W SLEEP (monitor + power brick): 1.5W OFF (monitor + power brick): 0.5W |
| Temperature | Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F) |
| Humidity | Operating: 20% to 80%; Storage: 10% to 95% |
| Weight | Unpackaged: 6.4 lbs (2.9 kg); Packaged: 7.7 lbs (3.4 kg) |
| Shipping Dimensions | 17.09" x 14.76" x 6.89" / 434mm x 375mm x 175mm |
| Mounting Options | 75mm and 100mm VESA mount; 2-hole mounting interface on all 4 sides; Rear mount (PCAP Models); Front mount with optional bezel kit (IT/AT/ST Models); Rack mount with optional bezel kit (IT/AT/ST Models); Flush mount with included brackets (PCAP Models) |
| Warranty | 3 years standard |
| MTBF | 50,000 hours demonstrated |
| Agency Approvals | UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; RoHS, China RoHS, WEEE, IMERC |
| What's in the Box | All displays include: VGA Cable, RJ45 OSD Remote, USB Touch Cable, User Manual CD and Quick Install Guide; For Zero-Bezel Models: Flush Mount Brackets w/Screws; For Bezeled Models: "L" (Side Mount) Brackets w/Screws |

Ordering Information

| Model | Part Number | Part Descriptions | Technology | Interface | Surface Treatment | Video Interface | Availability |
|-------|-------------|----------------------------|----------------------|-----------------|-------------------|-----------------|--------------|
| 1590L | E176164 | ET1590L-2UWA-0-MT-ZB-NPB-G | Projected Capacitive | USB | Clear | VGA & DP | Worldwide |
| | E196676 | ET1590L-8CWA-1-ST-NPB-G | IntelliTouch | Dual serial/USB | Antiglare | VGA & DP | Worldwide |
| | E176568 | ET1590L-6CWA-1-ST-NPB-G | SecureTouch | Dual serial/USB | Antiglare | VGA & DP | Worldwide |
| | E176751 | ET1590L-7CWA-1-ST-NPB-G | AccuTouch | Dual serial/USB | Antiglare | VGA & DP | Worldwide |

Extended Warranty Options

| Part Number | Description |
|-------------|--|
| 758588-000 | 1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor |
| 930057-000 | 2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor |
| E67295-000 | Elo advance unit replacement for touchmonitors |

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch, IntelliTouch, SecureTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17032AES00030

