

PRP-058C

Compact Thermal Receipt Printer









Fametech Inc. provides customers with wide variety of printers and welcomes OEM/ODM orders. We are able to prototype your desired specifications and eventually deliver high-quality printers in a reasonably short period of time. Custom logos, instructions and packages are all available upon request.



Your Reliable POS Solution Provider





Featured High Speed Receipt Printer

# **Empower Your Business**

TYSSO<sup>®</sup>
Beyond Mere POS

Fametech Inc.

2FL., No.165, Sec. 2, Ta-Tung Road, Hsi-Chih 221, Taipei Hsien, Taiwan

**Tel**: +886 2 8692 6300 | Fax: +886 2 8692 6301 **Email**: info@fametech.com.tw | tysso@ms6.hinet.net

www.fametech.com.tw



#### \* The alarm buzzer PBZ-100 is released, please visit our website for more information.

## PRP-058



- Graphic printing capability
- Print head speed: 50mm per second
- Print head reliability: 50km
- Paper width 57.5 ± 0.5 mm
- · Print column : 384 dots per line
- · Halt-on protection from overheat : 60°
- · Character per line : 32 (font A)
- · Dot density: 8 dots per millimeter

#### PRP-058C **Mini Thermal Receipt Printer Compact Thermal Receipt Printer**



- · Compact Thermal Receipt Printer
- · Print method : thermal line printing
- Print reliability : 100 km
- Print speed: 120 mm/sec
- Paper thickness: 0.06 0.08mm
- Paper width: 2-inch, 57.5 ± 0.5 mm Print columns : 384 dots/line
- Interface: Paralleled, Serial, LAN, USB
- Compatible with ESC/POS

#### PRP-076 Dot-Matrix Receipt Printer



- · Print speed: 4.5 lines per second
- · Max label width : 76mm ± 0.5mm
- Print density: 400DPL or 300 DPL
- Halt-on protection : 120°C
- · Print head reliability : 5 million lines Paper width: 76mm ± 0.5mm
- · Dimension : 260mm x 160mm x 132mm
- · Weights: 1600g (without cable)

## **Vertical Thermal Receipt Printer**



- · Print speed : 250 mm/sec
- · Print reliability : 100Km
- Print resolution : 576 dots/line
- · Effective print width : 72mm Paper width: 79.5, ± 0.5mm
- · Paper thickness: 0.06~0.08mm
- Print command : ESC/POS print
- commands set
- · Over-heat halt-on Protection: 80°C
- · Multi I/O interface (Serial + Ethernet + USB or Parallel + USB)

### PRP-250 **Glossy Thermal Receipt Printer**



- Glossy Thermal Receipt Printer
- Print speed : 250 mm/sec
- Print reliability: 100Km

commands set

- Print resolution: 567 dots/line Effective print width: 72mm
- Paper width: 79.5, ± 0.5mm Paper thickness: 0.06~0.08mm
- Print command : ESC/POS print
- Over-heat halt-on Protection: 80°C
- Multi I/O interface (Serial + Ethernet + USB or Parallel + USB)

## Featured High Speed Receipt Printer



- Print Method : Thermal line printing
- Print Speed: 250mm/sec
- Print Life: 100 Km
- Print resolution : 567 dots/line
- Character Per Line: 48 (Font A) / 64(Font B)
- Paper Width: 79.5mm± 0.5mm
- Paper Thickness: 0.06~0.08mm
- Print Command : ESC/POS print commands set
- · Multi I/O Interface (Serial +Ethernet + USB or Parallel +USB available)
- · Audio and LED Indicators
- Paper End Notice & Over-Heat Halt-on Protection